Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of the Claims

1 – (Currently Amended) A planar antenna with diversity of radiation realised on a substrate comprising a slot of closed shape dimensioned to operate on a mode higher than a fundamental mode and at least one feed-line coupled to said slot according to a line/slot transition, the perimeter of the slot being selected such that $p = k\lambda s$ where p is the perimeter of the slot, k is an integer greater than 4 or equal to 2 and λs is the guided wavelength in the slot, said antenna comprising a first feed-line coupled in a zone of the slot forming antirest open circuit and a second feed-line placed at a distance $d = (2n+1) \lambda s/4$ from said first line, where n is an integer greater than or equal to zero, said second feed line being coupled in a zone of the slot forming a first short-circuit, so that two complementary radiation patterns are obtained depending on the feed line selected for the access.

- 2 (Currently Amended) The antenna of claim 1, wherein each the first and second feed-lines terminates in ansecond and third open circuits and isare each coupled to the slot according to a line/slot transition, the length of each feed line after the line/slot transition being equal to $(2k'+1)\lambda m/4$ where λm is the guided wavelength under in the feed line and k' is a positive or null integer.
- 3 (Currently Amended) The antenna of claim 1, wherein each feed-line is coupled to the slot according to a line/slot transition with a microstrip line terminated by a second short-circuit, the length of each feed line after the line/slot transition being equal to k''λm/4 where λm is the guided wavelength under-in the feed line and k'' is a positive or null integer.

4 – (cancelled)

Amdt. dated November 3, 2008 Reply to Office Action of July 2, 2008

5 – (Currently Amended) The antenna of claim 1, wherein the feed-lines are realised in microstrip technology, or in coplanar technology or by a coaxial cable.

6 – (Previously Presented) The antenna of claim 1, wherein the shape of the

slot is an annular, square, rectangular, polygonal shape or is in a clover leaf form.

7 - (Previously Presented) The antenna of claim 6, wherein the slot is of

rectangular shape and the feed-lines are equidistant from an axis of symmetry of the slot.

8 - (Previously Presented) The antenna of claim 6, wherein the slot is of

rectangular shape and one of the feed-lines is positioned according to an axis of symmetry

of the slot.

9 – (Previously Presented) The antenna of the claim 1, where the feed lines are

connected to a transmission/reception means enabling a diversity of reception.

10 – (New) A planar antenna with diversity of radiation realised on a substrate

comprising a slot of closed shape dimensioned to operate on a mode higher than a

fundamental mode and at least one feed-line coupled to said slot according to a line/slot

transition, the perimeter of the slot being selected such that $p = k\lambda s$ where p is the perimeter

of the slot, k is an integer greater or equal to 2 and λ s is the guided wavelength in the slot,

said antenna comprising a first feed-line coupled in a zone of the slot forming first open

circuit and a second feed-line placed at a distance $d = (2n+1) \lambda s/4$ from said first line,

where n is an integer greater than or equal to zero, said second feed line being coupled in a

zone of the slot forming a first short-circuit, wherein each feed-line is coupled magnetically

to the slot according to a tangential line/slot transition.

11 – (New) The antenna of claim 10, wherein the feed-lines are realised in

microstrip technology or in coplanar technology.

12 - (New) The antenna of claim 10, wherein the shape of the slot is an

annular, square, rectangular, polygonal shape or is in a clover leaf form.

3

Ser. No. 10/564,929 PF030121

Amdt. dated November 3, 2008 Reply to Office Action of July 2, 2008

13 – (New) The antenna of claim 12, wherein the slot is of rectangular shape and the feed-lines are equidistant from an axis of symmetry of the slot.

14 – (New) The antenna of claim 10, where the feed lines are connected to a transmission/reception means enabling a diversity of reception.